

The Esco Airstream® Class II Biological Safety Cabinet is an effective solution in providing operator, product and environmental protection within laboratories and industrial facilities. With ...

The Esco Airstream® Plus Class II BSC - E series (AC2- E-TU) has tempered glass sidewalls that increases visibility and prevents the operator from experiencing a "boxed-in" feeling. This unit is also equipped with multi-piece, autoclavable work tray for easy cleaning process.

Stock Code: AC2-4E8 Class II cabinet Esco Airstream E-Series working width 1220mm, manual sliding sash, 1 fan, 0.16kW maximum power draw, 61.1dB noise level, no VHP ports, recirculating, no angled HEPA filter, with 2 years warranty

The Esco Airstream® Gen 3 Class II Biological Safety Cabinet (AC2) is an effective solution in providing operator, product and environmental protection. It also features stable and self-compensating airflow, despite building voltage fluctuations & filter loading.

The Esco Airstream® Gen 3 Class II Biological Safety Cabinet (AC2) is an effective solution in providing operator, product and environmental protection. It also features stable and self-compensating airflow, despite building voltage fluctuations & filter loading.

The Esco Airstream® Class II Biological Safety Cabinet is an effective solution in providing operator, product and environmental protection within laboratories and industrial facilities. With the presence of its DC ECM blower, this is the most energy-efficient Class II Biosafety Cabinet in the world with 70% energy savings compared to AC motor.

The Esco Airstream® Gen 3 Class II Biological Safety Cabinet (AC2) is an effective solution in providing operator, product and environmental protection. It also features stable and self-compensating airflow, despite building voltage ...

Esco AC2 Airflow: OK I: 0.45 m/s Socket: ON 15:34 Sash: OK D: 0.30 m/s Diagnostics button, to easily check the cabinet operating parameters and assist servicing. Multi Language: English, French, German, Spanish, Italian. Ambient air is pulled through front grille to create inflow, without going into the work surface.

??c ch?ng nh?n tiêu chu?n EN 12469, t? an toàn sinh h?c c?p II Esco Airstream® c?ng có l?p ph? ch?ng vi khu?n trên t?t c? b? m?t ???c s?n trong và ngoài t?.

Stock Code: AC2-4E8 Class II cabinet Esco Airstream E-Series working width 1220mm, manual sliding sash,



Esco ac2 4e8 Finland

1 fan, 0.16kW maximum power draw, 61.1dB noise level, no VHP ports, recirculating, no angled HEPA filter, with 2 years ...

Comprehensive Performance Testing At Esco 1. Key Switch 2. Esco Sentinel™ Gold Microprocessor Control System 3. Laminated Glass Motorized Sliding Sash Window 4. Stainless Steel Multi-piece Work Tray 5. Electrical Panel 6. Energy Efficient LED Lamps 7. Hole-free, Easy to Clean Side Tempered Glass 8. IV Bar Retrofit Kit Provision 9.

Web: <https://www.taolaba.co.za>

